

PBM 30 • 1" Angle Ring and Profile Bending Machine



PBM 30 1" Ring and Profile Bending Machine \$5,270

Bending metal tubes, pipes, channels or beams is fast and easy with a KAAST PBM machine. We have the right machine for your structural steel fabrication application.

The robust machine frame is constructed of rugged steel, machined after welding for rigidity, and all welds are stress relieved prior to machining. Precision bearings and large shaft diameters minimize deflection for precise bending.

Machines are ensured a long life due to their strong frame and world-class hydraulic and electrical components. The short cycle times are achieved by high torque drive system and machine speed. Flat spots are minimized by close roll stance, powerful guide rolls and hydraulic adjustments. This series also boasts low energy and maintenance costs by friction-free planetary swing guides.

Standard Configuration:

- Modular hardened bending rolls
- Foot pedal
- Tool kit



In-Stock Special
\$5,270!

Specifications

Shaft Ø	Ø30 mm (1.1")
Upper roll Ø	Ø148 mm (5.8")
Lower roll Ø	Ø118 mm (4.7")
Motor power	0.7/0.85 kW (1 Hp)
Bending speed	3-6 m/min (118-235"/min)
Dimensions (L/W/H)	650x500x1400 mm (26x20x56")
Weight	220 kg (480 lbs)

Model			PBM 30	
No	Profile Type	Unit	Dimensions	Min. bending diameter
1		mm	30 (1.2"), 10 (0.4")	900 (36"), 200 (8")
2		mm	50x10 (2x0.4"), 20x6 (0.75x0.25")	800 (32"), 300 (12")
3		mm	80x15 (3.1x0.6"), 30x6 (1.2x0.25")	700 (28"), 400 (16")
4		mm	NPU 50 (2")	400 (16")
5		mm	NPU 50 (2")	350 (14")
6		mm	50x6 (2x0.25"), 20x3 (0.75x0.1")	600 (24"), 400 (16")
7		mm	50x6 (2x0.25"), 20x3 (0.75x0.1")	600 (24"), 400 (16")
8		mm	40x3 (1.5x0.1"), 30x2 (1.2x0.08")	1200 (48"), 800 (32")
9		mm	50x30x3 (2x1.2x0.1") 40x20x2 (1.5x0.7x0.08")	1200 (48"), 800 (32")
10		mm	Ø30 (1.2"), Ø10 (0.4")	900 (36"), 200 (8")
11		mm	Ø60x1.5 (2.4x0.06") Ø25x1.5 (1x0.06")	1000 (40"), 600 (24")
12		mm	1 1/2" x 0.11", 1/4" x 0.07"	600 (24"), 300 (12")
13		mm	40x40x5 (1.5x1.5x0.2") 30x30x4 (1.2x1.2x0.15")	600 (24"), 300 (12")
14		mm	35x35x5 (1.4x1.4x0.2") 30x30x4 (1.2x1.2x0.15")	600 (24"), 400 (16")

