



CNC hydraulic swing beam shear with adjustable rake HAGS



- The 2 top and 4 bottom blades are hardened to ensure they stay sharp
- CEBELEC CYBTOUCH 6 controllers and Siemens electrical system
- Paired with a Hoerbiger hydraulic system

Specifications		HAGS 3106	HAGS 3110	HAGS 3113	HAGS 3116	HAGS 3120	HAGS 3125	HAGS 3140	HAGS 4106	HAGS 4110	HAGS 4113
		10' x 1/4"	10' x 3/8"	10' x 1/2"	10' x 5/8"	10' x 3/4"	10' x 1"	10' x 1.5"	13' x 1/4"	13' x 3/8"	13' x 1/2"
Cutting length	mm	3100 (122")						4100 (161")			
Capacity **	mm	6 (.23")	10 (.39")	13 (.51")	16 (.63")	20 (.78")	25 (1")	40 (1.6")	6 (.23")	10 (.39")	13 (.51")
Stroke/Min	1/min	16-24	12-22	11-20	9-16	7-13	6-10	2-4	14-22	10-17	9-15
Hold Downs	#	14					20			18	
Main drive motor	kW	11 (15 Hp)	22 (30 Hp)		30 (40 Hp)	37 (50 Hp)	45 (60 Hp)	75 (101 Hp)	11 (15 Hp)	22 (30 Hp)	
Blade Gap	mm	.05-.8	.05-1.3	.05-1.5	.05-1.9	.05-2.3	.05-3.0	.05-5.5	.05-.8	.05-1.3	.05-1.5
Backgauge	mm	1000 (39")						1000 (39")			
Width	mm	2315 (91")	2425 (95")	2570 (101")	2700 (106")		2725 (107")	3030 (119")	2315 (91")	2580 (102")	2700 (106")
Height	mm	2225 (88")	2250 (89")	2400 (94")	2450 (96")	2550 (100")	2900 (114")	4360 (172")	2320 (91")	2460 (97")	2600 (102")
Length	mm	4980 (196")	5100 (201")	5110 (201")	5210 (205")	5220 (205")	5250 (207")	6070 (239")	6000 (236")	6100 (240")	6120 (241")
Weight	kg	7250 (15,980 lbs)	10230 (22,550 lbs)	12650 (27,890 lbs)	16500 (36,380 lbs)	18900 (41,670 lbs)	27600 (60,850 lbs)	79000 (174,170 lbs)	10450 (23,040 lbs)	15100 (33,290 lbs)	18450 (40,680 lbs)
Item No.		9220120	9220121	9220122	9220123	9220124	9220128	9220129	9220125	9200130	9220126

*The above specifications are subject to change without prior notice. No liability for printing mistakes. Machine may be shown with optional equipment.