

# C-Turn 270/2000 · 17x78" Engine Lathe



The C-Turn engine lathes feature hardened and precision-ground guideways for accuracy and durability. This exceptionally low noise machine has a universal-type gearbox allowing for cutting metric, Whitworth, module, and diametrical threads with no need to change gears.

#### Standard Configuration:

- 3-axis digital readout
- 4-post toolholder
- Work light
- Coolant system
- Backsplash guard
- Chuck guard
- Footbrake
- Tool kit

#### Options installed on machine:

- Rapid Z
- Steady-rest
- Follow-rest
- Micrometer
- Taper attachment
- Quick change toolpost
- 20" 4-Jaw chuck



#### Specifications

Swing over bed	Ø540 mm (24")	
Swing over gap	Ø680 mm (30")	
Swing over carriage	Ø360 mm (17.5")	
Distance between centers	2000 mm (78")	
Chuck mount	D1-8	
Spindle bore diameter	Ø85 mm (3.3")	
Speeds	18 Steps	23-1293 rpm
	Inverter	20-1500 rpm
Bed width	350 mm (13.5")	
Axis travel: X	330 mm (12.8")	
Toolholder travel: Z	150 mm (5.85")	
Threading	Inches	(36) 4-56 TPI
	Metric	(24) 0.5-7 mm/pitch
	Diametral	(36) 8-112 D.P.
	Module	(16) 0.25-3.5 M.P.
Travels	Z	0.06-0.88 mm/rev (0.002-0.034"/rev)
	X	0.03-0.44 mm/rev (0.001-0.017"/rev)
Tailstock quill diameter	Ø75 mm (2.9")	
Tailstock quill travel	170 mm (6.6")	
Tailstock quill taper	MT5	
Main spindle motor	7.5 kW (10 Hp)	
Weight	3100 kg (6820 lbs)	

**From \$710\*/month!**

\*Based on 60 month lease. Rates subject to change without notice.



**KAAST Machine Tools Inc. | [www.KAAST-USA.com](http://www.KAAST-USA.com) | 610-441-7317**