KAAST

MGS

1350 | 1550 | 2050 | 2550 | 3050

Motorized Sheet Metal Shear

The MGS swing-beam metal shear features a heavy **welded frame** for enhanced rigidity and a **low-noise drive system**. Its parallel-guided, high-strength **alloy steel blades** are **hardened and ground** for lasting precision.

STANDARD CONFIGURATION

- Set of Blades
- Side Fence / 2 Front Support Arms
- Hold-Down System
- Single / Continuous Stroke Selector Switch
- Footswitch / Safety Equipment
- Motorized Back Gauge (Models 4 mm)
- Support Table (Models 4 mm)

OPTIONAL CONFIGURATION

- Cutting Line Illumination
- Light Curtain
- Pneumatic Sheet Support
- 180° Angle Gauge
- Motorized or NC Backgauge System
- Backgauge
- Piece Counter
- Special Blades

MGS		1350/3	2050/3	2050/4	2550/2	2550/4	3050/2	3050/4
		4' x 11 Ga	6' x 11 Ga	6' x 9 Ga	8' x 13 Ga	8' x 9 Ga	10' x 13 Ga	10' x 9 Ga
Cutting Length	mm	1350 (53")	2050 (81")		2550 (100")		3050 (120")	
Capacity	mm	3 (11 Ga)		4 (9 Ga)	2 (13 Ga)	4 (9 Ga)	2 (13 Ga)	4 (9 Ga)
Table Width	mm	390 (15")		455 (18")	390 (15")	455 (18")	390 (15")	455 (18")
Stroke / Min	1/min	35		41	35	41	35	41
Main Motor	kW	3 (4 Hp)	4 (5 Hp)	7.5 (10 Hp)	4 (5 Hp)	7.5 (10 Hp)	4 (5 Hp)	7.5 (10 Hp)
Backgauge	mm	750 (29")						
Dimensions (L/W)	mm	1930x2150 (76x85")	2700x2150 (106x85")	2700x2150 (106x85")	3200x2150 (126x85")		3700x2150 (146x85")	
Dimensions (H)	mm	1310 (52")		1450 (57")	1310 (52")	1450 (57")	1310 (52")	1450 (57")
Weight	kg	1260 (2,780 lbs)	1760 (3,880 lbs)	3010 (6,640 lbs)	1960 (4,320 lbs)	3510 (7,740 lbs)	2210 (4,870 lbs)	4010 (8,840 lbs)
Item No.		9221001	9221008	9221003	9221002	9221005	9221009	9221006

*The above specifications are subject to change without prior notice. No liability for printing mistakes. Machine may be shown with optional equipment.